



Investigation of 16 calibrated Valiantzas' evapotranspiration equations against standard FAO56-PM model in Indian humid climatic condition

Arvind Singh Tomar

Department of Irrigation and Drainage Engineering, College of Technology, GBPUAT, Pantnagar (Uttarakhand)

Corresponding author:

E-mail: arvindstomar@gmail.com (Arvind Singh Tomar)

ARTICLE INFO

DOI: 10.59797/ijsc.v51.i3.142

Article history:

Received : December, 2020

Revised : June, 2023

Accepted : June, 2023

Key words:

Calibration

Dehradun

Humid

Reference evapotranspiration

Valiantzas equations

ABSTRACT

The study was conducted with an objective to evaluate the performance of calibrated versions of different Valiantzas evapotranspiration (ET) equations over their original counterparts for humid climatic conditions prevailing at Dehradun district of Uttarakhand in comparison to standard FAO56-PM model as an index. The calibration coefficients were found to decrease in the range from 3.23% (Val 7) to 40.87% (Val 15). All calibrated Valiantzas equations (except Val 2, Val 7 and Val 13) showed significant increment in agreement index (D) between 0.01% (Val 5) and 34.84% (Val 15). With calibrated versions of Val 2, Val 7 and Val 13 equations, value of D was found to decrease to the tune of less than 1% with increased RMSE values, while calibrated versions of remaining 13 Valiantzas equations showed significant decrement in RMSE values. The calibrated versions of all Valiantzas equations showed reduction in MAXE values in between 14.29% (Val 7) to 84.55% (Val 15). Except Val 7 equation, the values of MBE and PE for calibrated Valiantzas equations decreased in the range from 87.22% (Val 16) to 196.49% (Val 6) and 3.49% (Val 6) and 93.32% (Val 15), respectively while SEE values with calibrated equations decreased in the range from 2.77% (Val 6) to 40.87% (Val 15). Almost all calibrated Valiantzas equations extended best R-values (near to 1.00) and they performed much better in comparison to their original versions.

1. INTRODUCTION

Water is becoming a scarce commodity with growing human population, severe neglect, and over-exploitation. It is estimated that annual national per capita availability of water in country has reduced from 1816 m³ in 2001 to 1544 m³ in 2011 (CWC, 2015) which is further expected to drop down to 1140 m³ in 2050 (Lal and Stewart, 2012). Similarly, exhaustion of groundwater in India has posed serious problems for groundwater managers in the form of drying of aquifers, groundwater pollution, salinity, saltwater intrusion, water table depletion, waterlogging, etc. It is also reported that in many parts of the country, water table is declining annually at the rate of 1-2 m (Singh and Singh, 2002). Due to all these issues of extremely serious nature, it is expected that availability of freshwater for domestic, irrigation, and industrial uses will reduce considerably and the country may face major water crisis in near future. Due to variation in climatic conditions and crop canopy, it is important to apply available irrigation water resources in such a way that

it will match crop water requirement substantially at different growth stages (Doorenbos and Pruitt, 1977).

Evapotranspiration (ET) is the sum of amount of water returned to the atmosphere through combined process of evaporation and transpiration (Hansen *et al.*, 1980; Watson and Burnett, 1995). It is one of the basic elements of hydrological cycle and is very essential and important parameter for scientific studies related to crop water requirement, development of best management practices for minimizing degradation of groundwater and surface water, irrigation scheduling, optimal crop production, management of irrigated areas & watershed, water budget etc. (Irmak *et al.*, 2003; Temesgen *et al.*, 2005; Ayttek, 2009; Chattopadhyay *et al.*, 2009; Sabziparvar and Tabari, 2010; Sabziparvar *et al.*, 2011).

The calculated values of ET help in determining reference evapotranspiration (ET₀), which can be estimated either with lysimeters or meteorological data (Lopez-Urrea *et al.*, 2006; Xing *et al.*, 2008) as it considers only evapora-

tive power of atmosphere at a specific location and time of year. The ET_0 values can directly be measured by lysimeter if change in soil moisture from known volume of soil is considered with vegetation (Watson and Burnett, 1995), but its use is very expensive, takes more time to install, and requires more maintenance. Therefore, researchers developed several methods to indirectly estimate ET_0 from observed meteorological parameters using large number of empirical or semi-empirical equations creating confusion to select any method as “standard” or “index”. Therefore, FAO proposed Penman-Monteith model in its Irrigation and Drainage Paper No. 56 (referred to as FAO56-PM model) as “standard” for determining ET_0 values.

Across the globe, researchers confirmed superior performance of FAO56-PM model in comparison to other ET_0 methods under different climatic conditions (Allen *et al.*, 1998; Walter *et al.*, 2000; Fontenot, 2004; Garcia *et al.*, 2004; Gavin and Agnew, 2004; Donatelli *et al.*, 2006; Popova *et al.*, 2006; Cai *et al.*, 2007; Ali and Shui, 2009; Xu *et al.*, 2013), however, serious limitation of FAO56-PM model is data requirement for a large number of meteorological parameters which are not always available for most locations, especially in developing countries (Wang *et al.*, 2007; Aytak, 2009).

Various scientists and researchers revealed a widely varying performance of available ET_0 equations under diverse climatic conditions and necessitated their local calibration (Allen *et al.*, 1998; Pereira *et al.*, 2006; Wang *et al.*, 2009) as these methods work optimally only for specific climatic conditions. The standard FAO56-PM model can be utilized to calibrate and validate empirical methods for new regions as per the recommendation of “FAO Expert Consultation on Revision of FAO Methodologies for Crop Water Requirements” (Smith *et al.*, 1992) and, therefore, calibration of existing ET_0 equations against a more reliable reference in the form of FAO56-PM model may provide a useful and powerful tool for estimating ET_0 values for agricultural and environmental related studies (Fontenot, 2004). A large number of available ET_0 equations were calibrated by researchers throughout the world for different climatic conditions considering standard FAO56-PM model as an index (Xu and Singh, 2000; Xu and Singh, 2002; Irmak *et al.*, 2003; Berengena and Gavilan, 2005; Trajkovic, 2005; Fooladmand and Haghighat, 2007; Trajkovic, 2007; Ahmadi and Fooladmand, 2008; Landaras *et al.*, 2008; Sepaskhah and Razzaghi, 2009; Zhai *et al.*, 2009; Lee, 2010; Tabari and Talaei, 2011; Ravazzani *et al.*, 2012; Thepadia and Martinez, 2012; Criestia *et al.*, 2013; Lima *et al.*, 2013; Mendicino and Senatore, 2013; Tabari *et al.*, 2013; Xu *et al.*, 2013; Heydari and Heydari, 2014; Heydari *et al.*, 2014; Kra, 2014; Valipour, 2015; Almorox and Grieser, 2016; Cobaner *et al.*, 2016; Ahooghalandari *et al.*, 2017; Cadro *et al.*, 2017; Feng *et al.*, 2017; Issaka *et al.*, 2017; Valipour, 2017).

From above, it is evident that various studies were conducted to calibrate ET_0 equations however, very little information is available for Indian conditions and no such study has been conducted with Valiantzas ET_0 equations for Indian humid locations. Therefore, in the present study, an attempt has been made to calibrate and evaluate the performance of 16 Valiantzas ET_0 equations at humid Dehradun district of Uttarakhand considering standard FAO56-PM model as an index.

2. MATERIALS AND METHODS

Study Area and Meteorological Dataset

The study on evaluation and calibration of different Valiantzas ET_0 equations was carried out for humid Dehradun district (78°04'E longitudes, 32°19'N latitudes and 516.5 m above msl) of Uttarakhand state using 31 years (1989-2019) of daily meteorological dataset consisting of air temperature (maximum and minimum), relative humidity (maximum and minimum), wind speed and actual sunshine hours. Prior to analysis, quality control of meteorological dataset was ensured by removing days with missing data and detecting outliers. For calibration purpose, 65% meteorological dataset (20 years, 1989-2008) was utilized while remaining 35% dataset of 11 years (2009-2019) was considered for validation purpose.

Reference Evapotranspiration (ET_0) Estimation

(a) FAO56-PM model: The recommended form of FAO 56-PM model consisting of aerodynamic and surface resistance terms (Allen *et al.*, 1998) is:

$$ET_0 = \frac{0.408\Delta(R_n - G) + \gamma \left(\frac{900}{T_{mean} + 273} \right) U_2 (e_s - e_a)}{\Delta + \gamma(1 + 0.34U_2)} \dots(1)$$

ET_0 is reference evapotranspiration (mm day^{-1}), Δ is slope of saturated vapour pressure curve ($\text{kPa } ^\circ\text{C}^{-1}$), R_n is net radiation at crop surface ($\text{MJ m}^{-2} \text{day}^{-1}$), G is soil heat flux density ($\text{MJ m}^{-2} \text{day}^{-1}$), γ is psychrometric constant ($\text{kPa } ^\circ\text{C}^{-1}$), T_{mean} is mean daily air temperature ($^\circ\text{C}$), U_2 is wind speed at 2 m height (m sec^{-1}), e_s is saturated vapour pressure (kPa), e_a is actual vapour pressure (kPa), and $e_s - e_a$ is vapour pressure deficit (kPa).

The nature of climate system allows soil heat flux (G) on daily timescale to be ignored as on daily basis, its value is nearly zero.

(b) Valiantzas ET_0 equations: The pertinent details of different Valiantzas equations considered in this study are presented in Table 1.

Calibration Coefficient Determination

In order to get calibration coefficient of different Valiantzas ET_0 equations considering standard FAO56-PM

Table:1
Details of considered Valiantzas ET₀ equations

S.No.	Mathematical form	Symbol	Reference
1.	$ET_0 = 0.051 \times (1 - \alpha) R_s \sqrt{T + 9.5} - 2.4 \times \left(\frac{R_s}{R_a}\right)^2 + 0.048 \times (T + 20) \times (1 - 0.01RH) \times (0.5 + 0.536U_2) + 0.00012Z$	Val 1	Valiantzas (2013b)
2.	$ET_0 = 0.051 \times (1 - \alpha) R_s \sqrt{T + 9.5} - 2.4 \times \left(\frac{R_s}{R_a}\right)^2 + 0.052 \times (T + 20) \times (1 - 0.01RH) \times (a_u - 0.38 + 0.54U_2)$	Val 2	Valiantzas (2006)
3.	$ET_0 = 0.051 \times (1 - \alpha) R_s \sqrt{T + 9.5} - 0.188 \times (T + 13) \left(\frac{R_s}{R_a} - 0.194\right) (1 - 0.00014 \times (0.70 \times T_{\max} + 0.30 \times T_{\min} + 46))^2 \times \sqrt{0.01RH} + 0.049 \times (T_{\max} + 16.3)(1 - 0.01RH)(0.50 + 0.536U_2)$	Val 3	Valiantzas (2006)
4.	$ET_0 = 0.051 \times (1 - \alpha) R_s \sqrt{T + 9.5} - 2.4 \times \left(\frac{R_s}{R_a}\right)^2 + 0.048 \times (T + 20) \times (1 - 0.01RH) \times (0.50 + 0.536U_2)$	Val 4	Valiantzas (2006)
5.	$ET_0 = 0.051 \times (1 - \alpha) R_s \sqrt{T + 9.5} - 2.4 \times \left(\frac{R_s}{R_a}\right)^2 - 0.024 \times (T + 20) \times (1 - 0.01RH) - 0.0165 \times R_s U_2^{0.7} + 0.0585 \times (T + 17) \times U_2^{0.75} \times [(1.03 + 0.00055TR^2) - 0.01RH] + 0.0001Z$	Val 5	Valiantzas (2013b)
6.	$ET_0 = 0.0393 \times R_s \sqrt{T + 9.5} - 2.4 \times \left(\frac{R_s}{R_a}\right)^2 - 0.024 \times (T + 20) \times (1 - 0.01RH) + 0.066 \times W_{\text{aero}} \times (T + 20) \times (1 - 0.01RH) U_2^{0.6}$	Val 6	Valiantzas (2013c)
	$W_{\text{aero}} = 0.78$, when $RH > 65\%$; and $W_{\text{aero}} = 1.067$, when $RH \leq 65\%$.		
7.	$ET_0 = 0.0393 \times R_s \sqrt{T + 9.5} - 0.19 \times R_s^{0.6} \varphi^{0.15} + 0.048 \times (T + 20) \times (1 - 0.01RH) U_2^{0.7}$	Val 7	Valiantzas (2013a)
8.	$ET_0 = 0.0393 \times R_s \sqrt{T + 9.5} - 2.4 \times \left(\frac{R_s}{R_a}\right)^2 + C_u \times (T + 20) \times (1 - 0.01RH)$ $C_u = 0.054$ when $RH > 65\%$; and $C_u = 0.083$ when $RH \leq 65\%$	Val 8	Valiantzas (2015)
9.	$ET_0 = 0.0393 \times R_s \sqrt{T + 9.5} - 0.19 \times R_s^{0.6} \varphi^{0.15} + 0.078 \times (T + 20) \times (1 - 0.01RH)$	Val 9	Valiantzas (2013a)
10.	$ET_0 = 0.0393 \times R_s \sqrt{T + 9.5} - 2.4 \times \left(\frac{R_s}{R_a}\right)^2 - 0.024 \times (T + 20) \times (1 - 0.01RH) + 0.1W_{\text{aero}}(T + 20) \times (1 - 0.01RH)$ $W_{\text{aero}} = 0.78$, when $RH > 65\%$; and $W_{\text{aero}} = 1.067$, when $RH \leq 65\%$	Val 10	Valiantzas (2013a)
11.	$ET_0 = 0.0393 \times R_s \sqrt{T + 9.5} - 2.4 \times \left(\frac{R_s}{R_a}\right)^2 + C_u \times (T + 20) \times (1 - 0.01RH)$ $C_u = 0.076 - 0.0119(RH - 50)^{0.2}$, when $RH > 50\%$; and $C_u = 0.076 + 0.0084(50 - RH)^{0.2}$, when $RH \leq 50\%$	Val 11	Valiantzas (2015)
12.	$ET_0 = 0.0393 \times R_s \sqrt{T + 9.5} - 0.19 \times R_s^{0.6} \varphi^{0.15} + 0.0061 \times (T + 20) \times (1.12T - T_{\min} - 2)^{0.7}$	Val 12	Valiantzas (2013b)

Table:1
Continued

S.No.	Mathematical form	Symbol	Reference
13.	$ET_0 = 0.0393 \times R_s \sqrt{T + 9.5} - 0.19 \times R_s^{0.6} \phi^{0.15} + 0.0059 \times (T + 20) \times (T - T_{min} - 0.45TR + 3.45)^{0.9}$	Val 13	Valiantzas (2015)
14.	$ET_0 = 0.038 \times R_s \sqrt{T + 9.5} - 2.4 \times \left(\frac{R_s}{R_a}\right)^2 + 0.075 \times (T + 20) \times (1 - 0.01RH)$	Val 14	Valiantzas (2013a)
15.	$ET_0 = 0.047 \times R_s \sqrt{T + 9.5} - 2.4 \times \left(\frac{R_s}{R_a}\right)^2 + 0.09 \times (T + 20) \times (1 - 0.01RH)$	Val 15	Valiantzas (2006)
16.	$ET_0 = 0.00668 \times R_s \sqrt{(T + 9.5)(T_{max} - T_{dew})} + 0.0696 \times (T_{max} - T_{dew}) - 0.024 \times (T + 20) \times (1 - 0.01RH) - 0.00455 \times R_a \sqrt{(T_{max} - T_{dew})} + 0.0984 \times (T + 17)(1.03 + 0.00055TR^2 - 0.01RH)$	Val 16	Valiantzas (2013b)

$$T_{dew} = T_{min} - 0.12T + 2$$

ET_0 is reference evapotranspiration ($mm\ day^{-1}$), α is albedo, R_s is solar radiation ($MJ\ m^{-2}\ day^{-1}$), R_a is extra-terrestrial radiation ($MJ\ m^{-2}\ day^{-1}$), T is mean air temperature ($^{\circ}C$), RH is relative humidity (%), U_2 is wind speed at 2 m height ($m\ sec^{-1}$), TR is temperature difference ($^{\circ}C$), Z is altitude above mean sea level (m), T_{dew} is dew point temperature ($^{\circ}C$), T_{max} is maximum air temperature ($^{\circ}C$), T_{min} is minimum air temperature ($^{\circ}C$), ϕ is latitude (radian), and U_a is long-term average wind speed ($m\ sec^{-1}$). Val 1 is Valiantzas 1, Val 2 is Valiantzas 2, Val 3 is Valiantzas 3, Val 4 is Valiantzas 4, Val 5 is Valiantzas 5, Val 6 is Valiantzas 6, Val 7 is Valiantzas 7, Val 8 is Valiantzas 8, Val 9 is Valiantzas 9, Val 10 is Valiantzas 10, Val 11 is Valiantzas 11, Val 12 is Valiantzas 12, Val 13 is Valiantzas 13, Val 14 is Valiantzas 14, Val 15 is Valiantzas 15, Val 16 is Valiantzas 16.

model as an index, following steps were taken in accordance with Tabari and Talaei (2011):

- (i) Calculating ratio of $ET_{0\ Val}$ to $ET_{0\ FAO56-PM}(R)$.

$$R = \frac{ET_{0\ Val}}{ET_{0\ FAO56-PM}}$$

- (ii) Multiplying inverse of this ratio (1/R) with original coefficient to get calibration coefficient.

- (iii) Calibrated ET_0 values were determined as:

$$\text{Calibrated } ET_0 = \frac{\text{Calibration coefficient} \times \text{Original value } ET_{0\ Val}}{\text{Original coefficient}} \dots(2)$$

- (iv) Repeating steps (i-iii) will yield calibration coefficients and ET_0 values of different considered Valiantzas equations.

Statistical Analysis

Details of various statistical indices used in this study to compare ET_0 values calculated by Valiantzas equations and standard FAO_{56-PM} model are presented in Table 2. MicrosoftTM Excel[®] was used as computing tool to analyse obtained results in order to draw fruitful interferences from them.

3. RESULTS AND DISCUSSION

Calibration Coefficient

The values of original coefficient, calibration coefficient and percent deviation of calibration coefficient with respect to original coefficient for different Valiantzas ET_0 equations (Table 3) shows that calibration coefficients

Table: 2
Computational form of considered statistical indices

Statistical index	Notation	Computational form
Agreement index	D	$1 - \frac{\sum_{i=1}^n (O_i - P_i)^2}{\sum_{i=1}^n (P_i - \bar{O} + O_i - \bar{O})^2}$
Root mean square error	RMSE	$\sqrt{\frac{\sum_{i=1}^n (P_i - O_i)^2}{n}}$
Maximum absolute error	MAXE	$\text{MAX}[O_i - P_i]_{i=1}^n$
Mean bias error	MBE	$\frac{1}{n} \sum_{i=1}^n (P_i - O_i)$
Percentage error of estimate	PE	$\left \frac{\bar{P} - \bar{O}}{\bar{O}} \right \times 100\%$
Standard error of estimate	SEE	$\left[\frac{\sum_{i=1}^n (O_i - P_i)^2}{n - 1} \right]^{0.5}$

$\bar{O}$ is mean of $FAO-56\ PM\ ET_0$ ($mm\ day^{-1}$), O_i is $FAO-56\ PM\ ET_0$ ($mm\ day^{-1}$), $\bar{P}$ is mean of $FAO-56\ PM\ ET_0$ ($mm\ day^{-1}$), P_i is predicted value of ET_0 ($mm\ day^{-1}$) estimated by using Valiantzas equations, n is total number of observations.

decreased in the range from 3.23% (Val 6) to 40.87% (Val 15). For Val 1, Val 2, Val 3, Val 4, and Val 5 equations, calibration coefficients as 0.04267, 0.04673, 0.04606, 0.04358 and 0.04918, respectively were lowered to the tune of 16.33%, 8.37%, 9.69%, 14.55% and 3.57% in comparison to their original coefficient (0.051), whereas for Val 6, Val 7, Val 8, Val 9, Val 10, Val 11, Val 12 and Val 13 equations, in comparison to their original coefficient (0.0393), about 3.23%, 5.37%, 23.51%, 23.69%, 23.51%, 24.27%, 26.64% and 20.59% lower values were obtained. Likewise, calibration coefficient for Val 14 and Val 15 equations were found 24.39% and 40.87% lower in comparison to their original coefficient of 2.4, while calibration coefficient of Val 16 equation (0.01618) was found 32.58% lower in comparison to its original coefficient (0.024).

Evaluation of Original and Calibrated Valiantzas ET₀ Equations vs FAO56-PM Model

The value of statistical indices and ratio (R) of ET₀ Val to ET₀ FAO56-PM obtained for all original and calibrated versions of Valiantzas equations (Table 4) reveal that in maximum cases, calibrated equations resulted in significant increment in value of D and decrement in errors (RMSE, MAXE, MBE, PE, and SEE) while value of R near to 1.00 indicated closer estimate of calibrated ET₀ equations in comparison to that obtained with standard FAO56-PM model. The calibra-

tion of Valiantzas equations revealed improvement in their performance as except Val 2, Val 7 and Val 13 equations, significant increment in D value was observed with all other considered equations in the range from 0.01% (Val 5) to 34.84% (Val 15), while its value decreased to the tune of less than 1.00% for these three equations. Similarly, in calibrated equations, RMSE values decreased in the range from 4.75% (Val 5) and 79.08% (Val 15), while calibrated Val 2 and Val 7 equations yielded increased RMSE value to the tune of 0.17% and 26.81%, respectively.

After calibration, the values of MAXE, MBE, PE and SEE decreased in the range from 14.29% (Val 7) to 84.55% (Val 15), 87.22% (Val 16) to 196.49% (Val 6), 3.49% (Val 6) to 93.32% (Val 15), and 2.77% (Val 6) to 40.87% (Val 15), respectively, whereas values of MAXE, MBE, and PE with calibrated Valiantzas equations were increased in the range of 0.17% (Val 2) to 26.81% (Val 7); 300.21% (Val 7), and 299.89% (Val 7) while no increment in SEE values with any calibrated Valiantzas equations was observed. In calibrated Valiantzas equations, value of ratio (R) gets lowered in the range from 3.58% (Val 5) to 40.87% (Val 15).

Except calibrated version of Val 16 equation, all other equations produced best results in terms of ratio (R) as near to 1.00 while, worst result was found with calibrated Val 16 equation (R = 1.12).

4. CONCLUSIONS

The performance of calibrated versions of 16 Valiantzas ET₀ equations for humid Dehradun district of Uttarakhand evaluated in comparison to standard FAO56-PM model in terms of statistical indices and ratio of ET₀ Val/ET₀ FAO56-PM (R) revealed that they extended higher value of D (0.01-34.84%) with lowered values of RMSE (4.75-79.08%), MAXE (14.29-84.55%), MBE (87.22-196.49%), PE (3.49-93.32%), and SEE (2.77-40.87%). Likewise, all calibrated Valiantzas equations (except Val 16) yielded best value of ratio (R) as near to 1.00. The study further confirmed that calibrated versions of Valiantzas ET₀ equations at humid Dehradun district of Uttarakhand should be preferred over their original counterparts for calculating at par FAO56-PM ET₀ estimates over their original counterparts.

REFERENCES

- Ahmadi, S.H. and Fooladmand, H.R. 2008. Spatially distributed monthly reference evapotranspiration derived from the calibration of Thornthwaite equation: A case study, South of Iran. *Irrig. Sci.*, 26(4): 303-312.
- Ahooghalandari, M., Khiadani, M. and Jahromi, M.E. 2017. Calibration of Valiantzas' reference evapotranspiration equations for the Pilbara region, Western Australia. *Theory Appl. Climatol.*, 128(3-4): 845-856.
- Ali, M.H. and Shui, L.T. 2009. Potential evapotranspiration model for Muda irrigation project, Malaysia. *Water Resour. Manage.*, 23: 57-69.

Table: 3
Original and calibration coefficients of Valiantzas ET₀ equations

S.No.	Equation(s)	Coefficient	
		Original	Calibration
1.	Val 1	0.051	0.04267 (-16.33%)
2.	Val 2		0.04673 (-8.37%)
3.	Val 3		0.04606 (-9.69%)
4.	Val 4		0.04358 (-14.55%)
5.	Val 5		0.04918 (-3.57%)
6.	Val 6	0.0393	0.03803 (-3.23%)
7.	Val 7		0.03719 (-5.37%)
8.	Val 8		0.03006 (-23.51%)
9.	Val 9		0.02999 (-23.69%)
10.	Val 10		0.03006 (-23.51%)
11.	Val 11		0.02976 (-24.27%)
12.	Val 12		0.02883 (-26.64%)
13.	Val 13		0.03121 (-20.59%)
14.	Val 14	2.4	1.81469 (-24.39%)
15.	Val 15		1.41906 (-40.87%)
16.	Val 16	0.024	0.01618 (-32.58%)

Val 1 is Valiantzas 1, Val 2 is Valiantzas 2, Val 3 is Valiantzas 3, Val 4 is Valiantzas 4, Val 5 is Valiantzas 5, Val 6 is Valiantzas 6, Val 7 is Valiantzas 7, Val 8 is Valiantzas 8, Val 9 is Valiantzas 9, Val 10 is Valiantzas 10, Val 11 is Valiantzas 11, Val 12 is Valiantzas 12, Val 13 is Valiantzas 13, Val 14 is Valiantzas 14, Val 15 is Valiantzas 15, Val 16 is Valiantzas 16.

Figures in parenthesis shows percent deviation in comparison to original coefficient, (+) represents increment and (-) shows decrement w.r.t. original coefficient.

Table: 4**Comparative performance of original and calibrated Valiantzas equations vs FAO56-PM model during validation period (2009-2019)**

S.No.	Equation(s)	Features	Statistical indices						R
			D	RMSE	MAXE	MBE	PE	SEE	
1	Val 1	Original	0.9677	0.4494	0.7800	0.4228	15.3798	0.1499	1.20
		Calibrated	0.9887	0.2400	0.2600	-0.0957	3.4814	0.1251	1.00
		% variation	2.17	-46.60	-66.67	-122.63	-77.36	-16.54	-16.36
2	Val 2	Original	0.9945	0.1784	0.3300	0.1524	5.5437	0.0864	1.08
		Calibrated	0.9940	0.1787	0.1600	-0.0904	3.2886	0.0793	0.99
		% variation	-0.05	0.17	-51.52	-159.32	-40.68	-8.22	-8.36
3	Val 3	Original	0.9901	0.2457	0.4300	0.2292	8.3354	0.0846	1.10
		Calibrated	0.9967	0.1355	0.1600	-0.0593	2.1557	0.0762	1.00
		% variation	0.67	-44.85	-62.79	-125.87	-74.14	-9.93	-9.68
4	Val 4	Original	0.9753	0.3915	0.7200	0.3607	13.1188	0.1503	1.17
		Calibrated	0.9904	0.2243	0.2400	-0.0920	3.3453	0.1287	1.00
		% variation	1.55	-42.71	-66.67	-125.51	-74.50	-14.37	-14.55
5	Val 5	Original	0.9975	0.1220	0.2818	0.0666	2.4234	0.1018	1.04
		Calibrated	0.9976	0.1162	0.1104	-0.0339	1.2317	0.0982	1.00
		% variation	0.01	-4.75	-60.82	-150.90	-49.17	-3.54	-3.58
6	Val 6	Original	0.9970	0.1350	0.3900	0.0541	1.9668	0.1156	1.02
		Calibrated	0.9974	0.1241	0.2200	-0.0522	1.8982	0.1124	0.98
		% variation	0.04	-8.07	-43.59	-196.49	-3.49	-2.77	-4.08
7	Val 7	Original	0.9860	0.2764	0.6300	-0.0484	1.7621	0.2455	1.01
		Calibrated	0.9766	0.3505	0.5400	-0.1937	7.0464	0.2324	0.96
		% variation	-0.95	26.81	-14.29	300.21	299.89	-5.34	-5.38
8	Val 8	Original	0.9028	0.8757	1.8714	0.7619	27.7146	0.3623	1.32
		Calibrated	0.9834	0.3031	0.4628	-0.0636	2.313	0.2771	1.01
		% variation	8.93	-65.39	-75.27	-108.35	-91.65	-23.52	-23.51
9	Val 9	Original	0.9109	0.7623	1.4025	0.6321	22.9922	0.4255	1.32
		Calibrated	0.9534	0.4729	0.6629	-0.1689	6.1441	0.3247	1.00
		% variation	4.67	-37.96	-52.73	-126.72	-73.28	-23.69	-23.69
10	Val 10	Original	0.9032	0.8732	1.864	0.7604	27.6611	0.3606	1.32
		Calibrated	0.9834	0.3027	0.4571	-0.0647	2.3539	0.2758	1.01
		% variation	8.88	-65.33	-75.48	-108.51	-91.49	-23.52	-23.51
11	Val 11	Original	0.9071	0.8272	1.9754	0.7469	27.167	0.3253	1.332
		Calibrated	0.9794	0.3259	0.4957	-0.1018	3.7026	0.2463	1.01
		% variation	7.97	-60.60	-74.91	-113.63	-86.37	-24.29	-24.28
12	Val 12	Original	0.8886	0.8397	1.4283	0.7862	28.5984	0.2773	1.39
		Calibrated	0.9489	0.4682	0.6379	-0.1557	5.6618	0.2034	1.02
		% variation	6.79	-44.24	-55.34	-119.80	-80.20	-26.65	-26.64
13	Val 13	Original	0.9501	0.5158	1.0296	0.4527	16.4683	0.1575	1.25
		Calibrated	0.9483	0.4672	0.583	-0.2064	7.507	0.125	0.99
		% variation	-0.19	-9.42	-43.38	-145.59	-54.42	-20.63	-20.59
14	Val 14	Original	0.9033	0.8285	1.5234	0.7692	27.9789	0.2952	1.35
		Calibrated	0.9772	0.3358	0.4455	-0.0889	3.2325	0.2232	1.02
		% variation	8.18	-59.47	-70.76	-111.56	-88.45	-24.39	-24.39
15	Val 15	Original	0.7198	1.7914	3.0658	1.7074	62.1048	0.3859	1.73
		Calibrated	0.9706	0.3748	0.4737	-0.1141	4.1515	0.2282	1.02
		% variation	34.84	-79.08	-84.55	-106.68	-93.32	-40.87	-40.87
16	Val 16	Original	0.7350	1.7989	3.6100	1.6393	59.6299	0.4850	1.66
		Calibrated	0.9748	0.3886	0.99	0.2095	7.6218	0.327	1.12
		% variation	32.63	-78.40	-72.58	-87.22	-87.22	-32.58	-32.58

D is Agreement index, *RMSE* is Root mean square error (mm day^{-1}), *MAXE* is Maximum absolute error (mm day^{-1}), *MBE* is Mean bias error (mm day^{-1}), *PE* is Percentage error of estimate (%), *SEE* is Standard error of estimate, *R* is Ratio of $ET_{0 \text{ Val}}/ET_{0 \text{ FAO56-PM}}$. Val 1 is Valiantzas 1, Val 2 is Valiantzas 2, Val 3 is Valiantzas 3, Val 4 is Valiantzas 4, Val 5 is Valiantzas 5, Val 6 is Valiantzas 6, Val 7 is Valiantzas 7, Val 8 is Valiantzas 8, Val 9 is Valiantzas 9, Val 10 is Valiantzas 10, Val 11 is Valiantzas 11, Val 12 is Valiantzas 12, Val 13 is Valiantzas 13, Val 14 is Valiantzas 14, Val 15 is Valiantzas 15, Val 16 is Valiantzas 16.

- Allen, R.G., Pereira, L.S., Raes, D. and Smith, M. 1998. *Crop evapotranspiration - guidelines for computing crop water requirements*. FAO Irrigation and Drainage Paper No. 56, Rome, Italy, 300p.
- Almorox, J. and Grieser, J. 2016. Calibration of the hargreaves-Samani method for the calculation of reference evapotranspiration in different Koppen climate classes. *J. Hydro.*, 47(2):521-531.
- Aytek, A. 2009. Co-active neurofuzzy inference system for evapotranspiration modeling. *Soft Compu.*, 13: 691-700.
- Berengena, J. and Gavilan, P. 2005. Reference evapotranspiration estimation in a highly advective semi-arid environment. *J. Irrig. Drain. Engg.*, 131(2): 147-163.
- Cadro, S., Uzunovic, M., Zurovec, J. and Zurovec, O. 2017. Validation and calibration of various reference evapotranspiration alternative methods under the climate conditions of Bosnia and Herzegovina. *Inter. Soil Water Conser. Res.*, 5(4):309-324.
- Cai, J., Liu, Y., Lei, T. and Pereira, L.S. 2007. Estimating reference evapotranspiration with the FAO Penman-Monteith equation using daily weather forecast messages. *Agric. Forest Meteorol.*, 145: 22-35.
- Chattopadhyay, S., Jain, R. and Chattopadhyay, G. 2009. Estimating potential evapotranspiration from limited weather data over Gangetic West Bengal, India: A neurocomputing approach. *Meteorol. Appl.*, 16(3): 403-411.
- Cobaner, M., Citakoglu, H., Haktanir, T. and Kisi, O. 2016. Modifying hargreaves-samani equation with meteorological variables for estimation of reference evapotranspiration in Turkey. *Hydrol. Res.*, 47(2): 480-497.
- Criestia, N.C. Kampf, S.K. and Burges, S.J. 2013. Revised coefficients for Priestley - Taylor and Makkink-Hansen equations for estimating daily reference evapotranspiration. *J. Hydrol. Engg.*, 18(10): 1289-1300.
- CWC. 2015. Water and Related Statistics. www.cwc.gov.in/main/downloads/Water_Related_Statistics_2015.pdf (Accessed on Oct 25, 2020).
- Donatelli, M., Bellocchi, G. and Carlini, L. 2006. Sharing knowledge via software components: Model on reference evapotranspiration. *J. Euro. Agro.*, 24: 186-192.
- Doorenbos, J. and Pruitt, W.O. 1977. Guidelines for predicting crop water requirements. Irrigation and drainage Paper No. 24, 2nd ed., FAO, Rome, Italy.
- Feng, Y., Jia, Y., Cui, N., Zhao, L., Li, C. and Gong, D. 2017. Calibration of Hargreaves model for reference evapotranspiration estimation in Sichuan basin of southwest China. *Agril. Water Manage.*, 181:1-9.
- Fontenot, R.L. 2004. An evaluation of reference evapotranspiration models in Louisiana. Unpublished MS thesis, Louisiana State University and A&M College, Baton Rouge, La.
- Fooladmand, H.R. and Haghghat, M. 2007. Spatial and temporal calibration of Hargreaves equation for calculating monthly ET₀ based on Penman-Monteith model. *Irrig. Drain.*, 56(4): 439-449.
- Garcia, M., Raes, D., Allen, R.G. and Herbas, C. 2004. Dynamics of reference evapotranspiration in the Bolivian highlands (Altiplano). *Agric. Forest Meteorol.*, 125(1-2): 67-82.
- Gavin, H. and Agnew, C.A. 2004. Modelling actual, reference and equilibrium evaporation from a temperate wet grassland. *Hydrol. Process*, 18(2): 229-246.
- Hansen, V.E., Israelsen, O.W. and Stringham, G.E. 1980. *Irrigation Principles and Practices*, 4th ed., John Wiley and Sons, Inc., New York.
- Heydari, M.M. Aghamajidi, R., Beygipoor, G. and Heydari, M. 2014. Comparison and evaluation of 38 equations for estimating reference evapotranspiration in an arid region. *Fresen. Environ. Bull.*, 23(8A): 1985-1996.
- Heydari, M.M. and Heydari, M. 2014. Calibration of Hargreaves-Samani equation for estimating reference evapotranspiration in semiarid and arid regions. *Arch. Agro. Soil Sci.*, 6(5): 695-713.
- Irmak, S., Irmak, A., Allen, R.G. and Jones, J.W. 2003. Solar and net radiation-based equations to estimate reference evapotranspiration in humid climates. *J. Irrig. Drain. Engg.*, 129(5): 336-347.
- Issaka, A.I., Paek, J., Abdella, K., Pollanen, M., Huda, A.K.S., Kaitibie, S., Goktepe, I., Haq, M.M. and Moustafa, A.T. 2017. Analysis and calibration of empirical relationships for estimating evapotranspiration in Qatar: Case study. *J. Irrig. Drain. Engg.*, 143(2): 05016013.
- Kra, E. 2014. FAO-56 Penman-Monteith daily ET₀ from linear regression calibrated Hargreaves equation with wind terms in tropics with limited data. *Inter. J. Agron.*, 1-9.
- Lal, R. and Stewart, B.A. 2012. *Soil Water and Agronomic Productivity*, CRC Press, 584p.
- Landeras, G., Ortiz-Barredo, A. and Lopez, J.J. 2008. Comparison of artificial neural network models and empirical and semi-empirical equations for daily reference evapotranspiration estimation in the Basque Country (Northern Spain). *Agril. Water Manage.*, 95(5): 553-565.
- Lee, K.H. 2010. Relative comparison of the local recalibration of the temperature-based evapotranspiration equation for the Korea Peninsula. *J. Irrig. Drain. Engg.*, 136(9): 585-594.
- Lima, J.R.D.S., Antonio, A.C.D., De Souza, E.S., Hammecker, C., Montenegro, S.M.G.L. and De Oliveira Lira, C.A.B. 2013. Calibration of Hargreaves-Samani equation for estimating reference evapotranspiration in sub-humid region of Brazil. *J. Water Resour. Protec.*, 5(12A):1-5.
- Lopez-Urrea, R., Martin de Santa Olalla, F., Fabeiro, C. and Moratalla, A. 2006. An evaluation of two hourly reference evapotranspiration equations for semiarid conditions. *Agril. Water Manage.*, 86(3): 277-282.
- Mendicino, G. and Senatore, A. 2013. Regionalization of the Hargreaves coefficient for the assessment of distributed reference evapotranspiration in southern Italy. *J. Irrig. Drain. Engg.*, 139(5): 349-362.
- Pereira, A.R., Green, S. and Villa Nova, N.A. 2006. Penman-Monteith reference evapotranspiration adapted to estimate irrigated tree transpiration. *Agric. Water Manage.*, 83(1-2):153-161.
- Popova, Z., Kercheva, M. and Pereira, L.S. 2006. Validation of the FAO methodology for computing ET₀ with limited data: Application to south Bulgaria. *Irrig. Drain.*, 55: 201-215.
- Ravazzani, G., Corbari, C., Morella, S., Gianoli, P. and Mancini, M. 2012. Modified Hargreaves-Samani equation for the assessment of reference evapotranspiration in Alpine River Basins. *J. Irrig. Drain. Engg.*, 138(7): 592-599.
- Sabziparvar, A.A. and Tabari, H. 2010. Regional estimation of reference evapotranspiration in arid and semi-arid regions. *J. Irrig. Drain. Engg.*, 136: 724-731.
- Sabziparvar, A.A., Mirmasoudi, S.H., Tabari, H., Nazemosadat, M.J. and Maryanaji, Z. 2011. ENSO teleconnection impacts on reference evapotranspiration variability in some warm climates of Iran. *Inter. J. Climatol.*, 31(11): 1710-1723.
- Sepaskhah, A. and Razzaghi, F. 2009. Evaluation of the adjusted Thornthwaite and Hargreaves-Samani methods for estimation of daily evapotranspiration in a semi-arid region of Iran. *Arch. Agro. Soil Sci.*, 55(1): 51-66.
- Singh, D.K. and Singh, A.K. 2002. Groundwater situation in India: Problems and perspective. *Inter. J. Water Resour. Manage.*, 18(4): 563-580.
- Smith, M., Allen, R.G., Monteith, J.L., Pereira, L.S., Perrier, A. and Pruitt, W.O. 1992. *Report on the Expert Consultation on Procedures for Revision of FAO Guidelines for Prediction of Crop Water Requirements*. Land and Water Development Division, UN-FAO, Rome, Italy, 40p.
- Tabari, H. and Talaei, P.H. 2011. Local calibration of the Hargreaves and Priestley-Taylor equations for estimating reference evapotranspiration in arid and cold climates of Iran based on the Penman-Monteith model. *J. Hydrol. Engg.*, 16(10): 837-845.
- Tabari, H., Talaei, P.H. and Some, B. 2013. Spatial modelling of reference evapotranspiration using adjusted Blaney-Criddle equation in an arid environment. *Hydrol. Sci. J.*, 58(2): 408-419.

- Temesgen, B., Eching, S., Davidoff, B. and Frame, K. 2005. Comparison of some reference evapotranspiration equations for California. *J. Irrig. Drain. Engg.*, 131: 73-84.
- Thepadia, M. and Martinez, C.J. 2012. Regional calibration of solar radiation and reference evapotranspiration estimates with minimal data in Florida. *J. Irrig. Drain. Engg.*, 138(2): 111-119.
- Trajkovic, S. 2005. Temperature-based approaches for estimating reference evapotranspiration. *J. Irrig. Drain. Engg.*, 131(4): 316-323.
- Trajkovic, S. 2007. Hargreaves versus Penman-Monteith under humid conditions. *J. Irrig. Drain. Engg.*, 133(1): 38-42.
- Valiantzas, J.D. 2006. Simplified versions for the Penman evaporation equation using routine weather data. *J. Hydrol.*, 331(3-4):690-702.
- Valiantzas, J.D. 2013a. Simple ET_0 forms of Penman's equation without wind and/or humidity data. I: Theoretical Development. *J. Irrig. Drain. Engg.*, 139(1): 1-8.
- Valiantzas, J.D. 2013b. Simplified forms for the standardized FAO-56 Penman-Monteith reference evapotranspiration using limited data. *J. Hydrol.*, 505: 13-23.
- Valiantzas, J.D. 2013c. Simplified reference evapotranspiration formula using an empirical impact factor for Penman's aerodynamic term. *J. Hydrol. Engg.*, 18(1): 108-114.
- Valiantzas, J.D. 2015. Simplified limited data Penman's ET_0 formulas adapted for humid location. *J. Hydrol.*, 524: 701-707.
- Valipour, M. 2015. Investigation of Valiantzas' evapotranspiration equation in Iran. *Theor. Appl. Climatol.*, 121(1): 267-278.
- Valipour, M. 2017. Calibration of mass transfer-based models to predict reference crop evapotranspiration. *Appl. Water Sci.*, 7(2): 625-635.
- Walter, I.A., Allen, R.G., Elliott, R., Jensen, M.E., Itenfisu, D., Mecham, B., Howell, T.A., Snyder, R., Brown, P., Eching, S., Spofford, T., Hattendorf, M., Cuenca, R.H., Wright, J.L. and Martin, D. 2000. *ASCE's Standardized Reference Evapotranspiration Equation*. In: Proc. 4th National Irrigation Symposium, ASAE, Phoenix, AZ.
- Wang, Y.M., Namaona, W., Traore, S. and Zhang, Z.C. 2009. Seasonal temperature-based models for reference evapotranspiration estimation under semi-arid condition of Malawi. *African J. Agric. Res.*, 4(9): 878-886.
- Wang, Y.M., Traore, S. and Kerh, T. 2007. *Determination of a reference model for estimating evapotranspiration in Burkina Faso*. In: Proc. 6th WSEAS International Conference on Artificial Intelligence, Knowledge Engineering and Databases, Corfu Island, Greece.
- Watson, I. and Burnett, A.D. 1995. *Hydrology: An Environmental Approach*. Boca Raton, FL: CRC Press.
- Xing, Z., Chow, L., Meng, F., Rees, H.W., Monteith, J. and Lionel, S. 2008. Testing reference evapotranspiration estimation methods using evaporation pan and modeling in maritime region of Canada. *J. Irrig. Drain. Engg.*, 134(4): 417-424.
- Xu, C.Y. and Singh, V.P. 2000. Evaluation and generalization of radiation-based methods for calculating evaporation. *Hydrol. Process*, 14(2): 339-349.
- Xu, C.Y. and Singh, V.P. 2002. Cross comparison of empirical equations for calculating potential evapotranspiration with data from Switzerland. *Water Resour. Manage.*, 16(3):197-219.
- Xu, J., Peng, S., Ding, J. Wei, Q. and Yu, Y. 2013. Evaluation and calibration of simple methods for daily reference evapotranspiration estimation in humid East China. *Arch. Agro. Soil Sci.*, 59(6): 845-858.
- Zhai, L., Feng, Q., Li, Q. and Xu, C. 2009. Comparison and modification of equations for calculating evapotranspiration (ET) with data from Gansu province, northwest China. *Irrig. Drain.*, 10.1002/ird.502.